






PC QUICK-FIT TERMINALS











.250 HORIZONTAL









MATERIAL:

.012 Brass, Nickel Plate

CAT. NO.	ACCEPTS TAB
3545	.110 × .020
3549	.110 × .032
	•



MATERIAL:

.012 Brass, Nickel Plate

CAT. NO.	ACCEPTS TAB
3546	$.205 \times .020$
3550	$.205 \times .025$
	$.205 \times .032$



-.067 DIA.


MATERIAL:

.016 Brass, Nickel Plate


CAT. NO.	ACCEPTS TAB
3547	$.250 \times .032$




.110 VERTICAL



.205 VERTICAL







.250 VERTICAL

MATERIAL:

.012 Brass, Nickel Plate

CAT. NO.	ACCEPTS TAB
3534	.110 × .020
3544	.110 × .032



MATERIAL: Brass, Nickel Plate

CAT. NO.	ACCEPTS TAB	MAT'L THICK	
	$.205 \times .020$		
3522	$.205 \times .025$.016	
	.205 × .025 .205 × .032	.016	




MATERIAL:

.016 Brass, Nickel Plate

CAT. NO.	ACCEPTS TAB
3528	.250 × .032



.187 VERTICAL




MATERIAL:

.016 Brass, Nickel Plate

CAT. NO.	ACCEPTS TAB
3548	.187 × .020
3551	.187 × .032

Mounting Detail

QUICK-FIT FEMALES



		_
MATERIAL:	Tinned	Brass


	CAT. NO.	A DIM TAB SIZE	B DIM LENGTH	AWG SIZE	MAT'L THICK
	1252	.110 × .020	.640	18-22	.010
	1264	$.187 \times .020$.576	16-22	.013
ı	4469	$.205 \times .020$.640	16-20	.013
l	4470	$.250 \times .032$.750	16-20	.016

.250 QUICK-FIT VINYL BOOT



Easily slips over terminalInsulated and protects


CAT. NO.	BOOT COLOR
4471	CLEAR
4472	RED
4473	BLUE
4474	YELLOW



MALE "QUICK-FIT" INSERTION TOOL

Designed to install .250 male "Quick-Fit" terminals quickly and easily

- Insert terminal into slot, spring clip will hold terminal securely for positioning
- Align terminal with mounting holes and "press-fit" to secure firmly in place
- · Lift tool to release terminal



CAT. NO. 1288